

TREE SWING INSTALLATION INSTRUCTIONS -WOOD TREE SWINGS AND CRAFTY THINGS-

- Once you have found a suitable place to hang your tree swing, you will need to loop your rope over the limb or structure to hang the swing.
- Using the supplied threaded U-bolt (1 per rope side), slide the U-bolt on from the cut side of the rope. This will compress the 2 ropes together. (See picture)



- Tighten the nuts on the U-bolt evenly using an adjustable wrench, 17mm or 11/16 wrench or socket can also be used.

Thank You for shopping with us and we appreciate your business!

Special Instructions for Teak Oiled and Watersealed Swings:

-On our swings which have watersealer applied to them (Poplar, Pine, Cherry and Distressed Styles), it is recommended that watersealer is reapplied once a year to maintain the look and protection of the wood.

-On our swings which have Teak Oil applied to them (Sapele Swings{all Sapele products}, Red Oak swings and our Oakipele swing styles), it is recommended that Teak Oil be reapplied twice a year to maintain the look and protection of the wood. Teak Oil is available at your favorite hardware store.

About Returns:

-If for some reason you decide to return your swing within 30 days, please make sure to include all items that were shipped with your swing (ie..clamps, rope..etc). A full refund minus our shipping cost to you. A refund will be issued in the same form of payment as originally used for purchase.

About Exchanges:

-If you decide for some reason to exchange your swing, please be sure to include everything with the swing. Items such as rope clamps should be securely packaged. Free Shipping only applies to the original shipment. Customer is responsible for shipment to us, and for shipping the replacement swing back to them.